

**MINIMUM CYCLE SLIP AIRBORNE DIFFERENTIAL CARRIER
PHASE GPS ANTENNA**

Origin of the Invention

[0001] The invention described herein was made by an employee of the United States Government and may be manufactured and used by or for the Government for governmental purposes without the payment of any royalties thereon or therefore.

Field of the Invention

[0002] This invention relates to an airborne antenna system, and more specifically, to a GPS (global positioning system) antenna orientation device for use with airplanes.

Detailed Description of the Prior Art

[0003] In conducting airborne GPS surveying operations, it is important for the surveying equipment to be provided with their precise geographic location.

[0004] The global positioning system can be used to determine the position of a GPS antenna to within a few centimeters by using well developed carrier phase differential interferometric techniques between an aircraft mounted GPS antenna and a nearby surveyed GPS reference receiver. The satellites participating in determining each fix must be widely distributed in azimuth and elevation to achieve optimum geometry when computing each fix.

[0005] The GPS satellites are in orbit around the Earth which causes each of them to rise and set relative to the horizon. It is critically important that each satellite be visible

and its carrier signal and phase be tracked by both the aircraft and the ground reference station. The carrier signal and phase information is lost or adversely affected by aircraft orientation during banking maneuvers which cause the aircraft GPS antenna to be pointed in an unfavorable direction for some satellites. Loss of carrier signal or phase information from a satellite is termed a “cycle slip.” A cycle slip can occur by losing signal for as little as 1 billionth (1.0×10^{-9}) of a second. Longer periods of missing signal cause loss of multiple cycles.

[0006] GPS antenna are normally securely mounted to the aircraft and are not moveable relative to the aircraft. Accordingly, during maneuvering of the aircraft, cycle slips may occur. Principal factors which cause cycle slips in an airborne environment are: 1) reduced signal due to unfavorable antenna orientation, 2) the path between the antenna and satellite is blocked by aircraft structure (wing, etc.), 3) the signal arrives directly from the satellite and via reflection from nearby parts of the aircraft and the direct and reflected signals are equal amplitude and opposite in phase causing them to cancel each other.

[0007] A need exists to reduce cycle slips caused by weak signals which are introduced by the GPS antenna being oriented in a less than optimal way since a maneuvering aircraft will necessarily be rolling, pitching or yawing so that the antenna is not vertically oriented.

[0008] Traditionally, pilots are instructed to reduce the banking (i.e., turning) of the aircraft to 10 degrees or less in order to minimize cycle slips during surveying operations. While this method may work, it significantly reduces the maneuverability of the aircraft and may result in a large amount of time necessary in order for the pilot to reverse course

to continue with the surveying operation. For instance, for closely spaced survey flight lines, a turn called a 90-270 is typically employed. The 90-270 requires a total of 360 degrees of heading change to effect a course reversal. If a 30 degree bank required two minutes to complete, then a 10 degree limited bank would require approximately six minutes to complete.

[0009] As an example, considering surveying an area 5 kilometers by 5 kilometers with a remote sensing system which has a swath of approximately 240 meters. To cover this area with flight lines every 200 meters would require $5000/200$ or 25 total flight lines. A nominal survey speed of 3600 meters per minutes each flight line requires one minute and 24 seconds to cover for a total of approximately 35 minutes of flight. 24 turns will be required to occupy all the flight lines. If those turns are 30 degrees each and take two minutes to perform, the total required flight time will be $24*2 + 35$ or 1 hour and 23 minutes. If the turns were restricted to 10 degrees, then the required flight time would be $24*6 + 35$ or approximately 3 hours. In this example, more time would be spent maneuvering then surveying.

[00010] Accordingly, a need exists to provide for the ability to perform sharper turns in aircraft without losing the GPS fix.

Summary of the Invention

[00011] The present invention is directed to an antenna system for an aircraft for use with a global positioning system comprising: an aircraft having an aircraft attitude determination system providing attitude data relating to aircraft roll, a translation module connected to the aircraft attitude determination system receiving the attitude data and

outputting output data, a processor receiving the output data from the translation module and providing a drive signal, a controller receiving the drive signal from the processor an articulator driven by the controller, and antenna attached to the articulator driven by the controller oppositely to the aircraft roll.

Brief Description of the Drawings

[00012] The particular features and advantages of the invention as well as other objects will become apparent from the following description taken in connection with the accompanying drawings in which:

Figure 1 is a front plan view of an aircraft equipped with an antenna system in accordance with the present invention banked at an angle of about 45° to a horizon;

Figure 2 is a side perspective view of a portion of an airplane with the antenna mounted thereon;

Figure 2a is a functional block diagram of the invention;

Figure 3 is a front cross-sectional view of the antenna mount utilized in the preferred embodiment of the antenna system; and

Figure 4 is a side cross-sectional view of the antenna mount shown in Figure 3.

Detailed Description of the Drawings

[00013] Figures 1 shows a front view of an airplane 10 equipped with the preferred embodiment of an antenna system of the present invention which is shown in more detail in Figures 2-4.

[00014] Figure 2 and 2a show the front portion of the airplane **10** equipped with an articulating GPS antenna **12** supported by mount **14** which may be partially recessed in the fuselage as shown or otherwise installed on airplane **10**. A processor **16** in the form of a microprocessor based interface circuitry receives a signal from a data translation module **18** shown in Figure 2a. The data translation module **18** receives a signal from an aircraft attitude system **20** such as an aircraft attitude determination system, attitude indicator, and/or navigation system such as an inertial navigation system or otherwise.

[00015] The attitude system **20** shown in Figures 3 and 4, delivers aircraft roll data such as in the form of digital data or analog synchro data to the processor **16** (i.e., digital or analog data in an appropriate format). The processor **16** receives and decodes the delivered attitude data and provides a signal to the controller **15** which drives the articulator **22** so that the antenna **12** is moved in an opposite direction to the roll of the aircraft sensed by the aircraft sensor **20**. This has been found effective to maintain the GPS antenna **12** in a substantially vertical orientation in spite of roll occurring by the airplane **10**. Aircraft roll is defined as the angle of rotation of an airplane along its longitude axis relative to the horizon. It is a term known in the art.

[00016] The aircraft system **20** and translation module **18** as well as the processor **16** and articulator **22** are driven by the aircraft electrical system. The physical size of the mount **14** in a prototype is about 10 x 15 x 15 cm. The mount **14** may weigh about a pound, but after equipping with a radome **26** about two pounds. A range of rotation of approximately at least 45 degrees to counter aircraft roll in either direction has been tested.

[00017] In the preferred embodiment the processor **16** receives aircraft attitude information at least five times per second. However faster or slower refresh rates may be also be utilized.

[00018] The axis of rotation is centered on pivot **24** so as to pass through the phase center of the actual GPS antenna **12** wherein it introduced no more than a very small error. The attitude information is obtained from the onboard inertial navigation system of the aircraft.

[00019] Although a linear motor, such as servo motor **23**, may be utilized as shown in Figures 3-4, other articulators **22** may be utilized to position the antenna **12** in a vertical orientation. The servo motor **23** drives gears **25,27** which act on gear **29** which is illustrated connected to the bottom of the radome **26**. Table **31** is illustrated connected to radome **26** to provide data path to the aircraft **10**. Furthermore, the processor **16** or translator **18** may contain a feed back loop to limit hunting and a dead zone such as no movement for a change in idle of about 3-5 degrees may be provided to prevent excessive wear and tear of the articulator **22**.

[00020] Figure 1 shows an aircraft with the antenna **12** positioned relative to the aircraft **10** at an aircraft roll position of about 45° relative to the horizon **11**. In Figure 4, the radome **26** is positioned in phantom and illustrated as element **26a** which is opposite to the direction of roll of the aircraft **10** shown in Figure 1. As the aircraft **10** rolls one way, the articulator **22** drives the antenna **12** within the radome **26** in an opposite direction to maintain the antenna **12** in an optimum upright orientation.

[00021] Numerous alterations of the structure herein disclosed will suggest themselves to those skilled in the art. However, it is to be understood that the present disclosure

relates to the preferred embodiment of the invention which is for purposes of illustration only and not to be construed as a limitation of the invention. All such modifications which do not depart from the spirit of the invention are intended to be included within the scope of the appended claims.